Ecopro Color System

Color System_별색 인쇄용

기본적으로 로고 심볼의 연장색이며 자연을 상징할수 있도록 Eco Blue, Eco Green을 주조색으로 설정한다.

Impact Color는 전체 배색면적의 10% 이내로 구성해야 한다.

Pantone Color_별색 인쇄용

Pantone Color는 그래픽 아트 및 인쇄분야에서 사용하는 세계적인 표준 인쇄잉크의 색 지정방식이다. P 165C와 P BlackC는 에코프로의 대표 색상으로 각종 아이템에 적용되는 색상 규정이며, 재현 시 Pantone Color를 기준으로 하여 표현한다.
ex) 서식류, 홍보물 등의 별색인쇄 P 165C 와 P Black 를 기준으로 제작하며, 또한, 사인류, 정기 등의 인쇄방법 이외의 제작(도색, 자수 등)의 경우도 Pantone Color 규정에 준하여 제작한다.

Process Color_색분해 인쇄용

Process Color는 CMYK의 안료(잉크)에 기초한 색상구현 원리를 사용한다. CMYK는 Cyan, Magenta, Yellow , Black 네가지 색상을 혼합하여 표현하며, Process Color는 Pantone Color(별색)의 표현이 불가능한 경우에 제한적으로 사용되는 색상규정이다.
ex) 신문광고, 잡지광고, 실사출력물 등의 옵셋인쇄는 Process Color를 기준으로 제작한다.

Main Color_주조색

Eco Blue
Spot color
PANTONE 2945U
Process Color
c100 / m95 / y5 /k0

Eco Green
Spot color
PANTONE 381U
Process Color
c80 / m0 / y100 /k0

Sub Color_보조색

Eco Warm Gray
Spot color
PANTONE 552U
Process Color
c20 / m10 / y20 /k0

Eco Metalic sky
Spot color
PANTONE 550U
Process Color
c40 / m10 / y20 /k20

Eco Light Gray
Spot color
PANTONE 443U
Process Color
c20 / m10 / y10 /k50

Eco Dark Gray
Spot color
PANTONE 446U
Process Color
c20 / m10 / y10 /k80

Impact Color_강조색

Eco Impact Red
Spot color
PANTONE 186U
Process Color
c10 / m100 / y50 /k0